

# DH-EAC64

Wireless Access Controller



- Wireless Access Controller.
- Multi WAN-port mode.
- EAP Series AP Management.
- Flexible Forwarding Modes.
- Smart Roaming Features.
- Various kinds of network authentication methods.



## Series Overview

EAC Series Wireless Access Controller (AC) is well designed and positioned for SME network. It features gateway and AC function integration, reducing the number of devices and TCO in network. It comes with the standard granular user control management, comprehensive RF resource management, 24/7 wireless security control, fast roaming, strong QoS. When paired with EAP Series Access Point (AP), it serves as an ideal access control solution for WLAN access of SMB network.

## Functions

### Minimal WEB

Designed with a minimalist graphical WEB, easy to operate, which improves configuration efficiency.

### Strong Control of Network Traffic Flow

Limits the uplink and downlink bandwidth, and the speed of users, meeting the needs of network management.

### Robust Design

Built to last, the architecture of the switch makes it highly reliable, operating with high-efficiency non-stop.

## Technical Specification

### Hardware

PoE Power Supply	No
Ethernet Port	5
Ethernet Port Speed	10/100/1000 Mbps
Description of Function Slots	Port 1-5: 5 × 10/100/1000Base-T RJ-45
LAN Port	4 × 1000 Mbps (3 LAN ports can be switched to WAN ports)
WAN Port	1 × 1000 Mbps
Reset Button	1
Power Supply	Built-in power supply: 100–240 VAC, 50/60 Hz, 2 A
Power Consumption	Idling: 0.96 W Full load: 12 W
Protection	IP20

### Function

802.11 LAN Protocols	802.11n;802.11b;802.11ax;802.11a;802.11g;802.11ac
CAPWAP	Layer 2 network topology between an AP and AC Enable an AP to automatically discover an accessible AC Enable an AP to automatically download configurations from an AC
Roaming	Intra-AC roaming
Forwarding	Local forwarding Centralized forwarding
Wireless QoS	AP-based bandwidth control WLAN-based bandwidth control; User-based static and smart speed control Fair balancing
User Isolation	WLAN-based user isolation
User Management	Access control based on SSID user number

<b>RF Management</b>	Country code configuration Manual configuration of transmitting power Manual configuration of working channel Automatically allocation of working channel Scheduled reallocation of wireless channel
<b>WAN Port Function</b>	Dynamic IP Static IP PPPoE IP/Mask configuration MTU configuration TCP MSS configuration Network bandwidth configuration Gateway address assignment NQA configuration to probe address
<b>Multi-WAN Load Balancing</b>	Distributing network traffic equally; Ratio load balancing; Multi-link for load balancing
<b>Link Detection</b>	Enable and disable link detection ICMP probe TCP probe
<b>IP Routing</b>	Static routing Policy-based routing
<b>VPN</b>	L2TP VPN PPTP VPN
<b>DHCP Function</b>	DHCP Server DHCP Client
<b>Security</b>	Portal Authentication PPPoE Authentication IP/MAC Authentication IP/MAC Binding Intranet Anomaly Detection Intranet Attack Protection WAN Ping Forbid Virtual AP Multiple SSIDs SSID Hiding WPA/WPA2 WPA3 WEP(WEP/WEP128) TKIP
<b>QoS/ACL</b>	Traffic supervision Congestion management Congestion avoidance Traffic shaping IP-based speed limit Traffic classification
<b>Equipment Management</b>	Web Management TFTP FTP NTP System Log Ping

## Performance

<b>Default Number of Manageable APs</b>	64
<b>Maximum Number of Manageable APs</b>	64
<b>Maximum Number of Configurable APs</b>	64
<b>Users Capacity</b>	2K
<b>Firewall</b>	500 Mbps
<b>Encryption</b>	500 Mbps
<b>Forwarding Capability</b>	500 Mbps
<b>CPU Frequency</b>	880 MHz

<b>Processor</b>	Dual core
<b>MTBF</b>	40,000 hours
<b>Memory</b>	256 MB
<b>Flash</b>	16 MB
<b>Packet Buffer Size</b>	2 MB
<b>MAC Address List</b>	1024
<b>Entries of MAC Address Filtering Table</b>	32
<b>IPv4 Forwarding</b>	1 Gbps
<b>Static Routes</b>	200
<b>Max. Number of Static DNS Records</b>	256
<b>Max. Number of DDNS Records</b>	4
<b>Static ARP</b>	1K
<b>Dynamic ARP</b>	2K
<b>ACL</b>	1K
<b>L2TP Users</b>	128
<b>Max. Number of Tunnels</b>	128
<b>Max. Number of Sessions</b>	128
<b>Max. Number of Concurrent Connections</b>	200K
<b>New Connections</b>	6K
<b>Max. Number of Virtual Servers</b>	100
<b>Max. Number of Port Triggering</b>	20
<b>Aging Time of Port Triggering</b>	10 min
<b>Number of NAT</b>	30

## General

<b>Operating Temperature</b>	-20 °C to +55 °C (-4 °F to +131 °F)
<b>Operating Humidity</b>	5%–95% (RH), non-condensing
<b>Storage Temperature</b>	-40 °C to +70 °C (-40 °F to 158 °F)
<b>Storage Humidity</b>	5%–95% (RH), non-condensing
<b>Statics Protection</b>	Air discharge: 8 kV; Contact discharge: 6 kV
<b>Lighting Protection</b>	Common mode: 2 kV; Differential mode: 1 kV
<b>Net Weight</b>	1.42 kg (3.13 lb)
<b>Gross Weight</b>	1.86 kg (4.10 lb)
<b>Product Dimensions</b>	294 mm × 180 mm × 44mm (11.57" × 7.09" × 1.73") (L × W × H)
<b>Packaging Dimensions</b>	325 mm × 241 mm × 81 mm (12.80" × 9.49" × 3.19") (L × W × H)
<b>Installation</b>	Desktop mount
<b>Certifications</b>	CE; FCC

Dimensions (mm [inch])

